Technical Specifications			
Hardware Interface	LAN WAN		00 BaseTX Switch with VLAN 0 BaseTX port with a RJ-45 connector
WAN Protocol	PPPoE, DHCP, PPTP, Static IP		
NAT	Multi-NAT,DMZ, Port Redirection, Open Ports, Pass-thru (VPN, VoIP, NetMeeting, MSN messenger, ICQ, Quakeetc.)		
Firewall Features	Access Control, IP-based Packet Filtering, Stateful Packet Inspection, Denial of Service Prevention		
Virtual Private Network	IKE Key Management, IPSec, PPTP, L2TP, L2TP over IPSec Hardware-based DES/3DES Encryption; AES Encryption MPPE Encryption for PPTP; IPSec Authentication (MD5 and SHA-1) Remote Access VPN; VPN Pass Through; Up to 16 tunnels; RADIUS Support		
Routing Support	RIPv2, Configurable Static Route		
Network Features	DHCP server/relay, Dynamic DNS,Call Scheduling,RADIUS Client		
URL Filtering	URL Blocking by User-defined Keywords; Java/ActiveX Blocking; Zip/Exe files Blocking		
Management	Time Schedule Support; Web-based User Interface Command Line Interface (Telnet) Telnet Remote Access Support; SNMP Agent with MIB-II Built-in Diagnostic Function; Remote Firmware Upgrade Quick Start Wizard; Syslog Monitoring		
Max. Power Consumption Dimension (cm) Power		16.0*H3.67	Operating temperature:0° to 45° C (32° to 113 F) Operating humidity:90% maximum relative humidity, noncondensing

Web Configuration






Secured Internet Access



Versatile Management



Dynamic Domain Name Server



Virtual Private Network

