



RM-IPC1600 7 Inch IPC Tester

7 Inch IP Camera tester with Touch Screen. For IP/Analogue camera, PTZ control, easy to operate . Built in network testing tools (IP address search, PING test etc). Cable scan, easy to check the network cable, BNC cable problem, effective to solve the optical fiber transmission problem. working time lasts 16 hours, built in WIFI, support Onvif. 12V 2A power output for camera ,DC48V PoE power supply,5V 2A power output, HDMI output, Audio input and output, Network bandwidth testing, OSD menu rotates in 180 angle, OSD menu can be rotated in 180 angle by manual setting.

Model	RM-IPC1600
Display	7 inch Capacitive touch screen , resolution 800 (RGB) x 600
Network port	10/100M auto adjust. RJ45
WIFI	Built in WIFI, speeds150M, receive wireless camera image etc
IP camera type	ONVIF, ACTi, Dahua IPC-HFW2100P、 Hikvision,DS-2CD864-E13、 Samsung SNZ-5200、 Tiandy TD-NC9200S2、 Kodak IPC120L、 Honeywell HICC-2300T、 Aipu-waton IP5000-BC-13MP/IRS06-13MP、 fine-Tida IPC、 FSJ BY-1080Q、 WEISKY IPC camera etc. Customized welcome
Video level test	1 channel BNC Input & 1 channel Output , NTSC/PAL (Auto adapt)
Video level meter	PEAK video signal level, SYNC signal level, COLOR BURST chroma level measurement
Zoom Image	Support Analog camera and IP camera image zoom /move
Snapshots,Video record,Record playback	Image Screenshots, record ,save ,view and record play back
HDMI output	1 channel HDMI output, support 1920*1080P
12V/2A power output	Output DC12V/2A power for camera
5V power output	5V 2A power output, as a mobile phone Power bank
PoE power output	48V PoE power output, Max power 24W。
Audio test	1 channel audio signal input, test whether sound normal, 1 channel audio signal, to connect headphone
PTZ control	Support RS232/RS485 control, Baud 600-115200bps, Compatible with more than 30 protocols such as PELCO-D/P, Samsung, Panasonic, Lilin, Yaan, etc
Video Signal Generator	Output one channel PAL/NTSC color bar video signal for testing monitor or video cable.(red, green ,blue, white and black color)
Network color bar generator	Local side PC can login the tester, send the signal by network ,test network connection communication whether normal
UTP Cable tester	Test UTP cable connection status and display in the screen. Read the number on the screen
Data monitor	Captures and analyzes the command data from controlling device, also can send hexadecimal
Network test	IP address scan, link scan, Ping test, Quickly search the connection IP camera and other device's IP address
Cable scan	Search the cable by the audio signal
PoE test	Measurement POE switch or PSE power supply voltage and cable connection status
POWER	
Power Supply	DC 12V 2A
Battery	Built-in 7.4V Lithium polymer battery ,6500mAh, Normal Working 16hs after recharge
Parameter	
Operation setting	Capacitive touch screen, OSD menu, Chinese/English
Auto off	1-30 (mins)
General	
Working Temp	-10℃---+50℃
Working Humidity	30%-90%
Dimension/Weight	231mm x 172mm x 52mm / 1.26Kg
Package Info	1pcs/ Carton dimension 34cmx31cmx14cm / Gross weight 3.5kg 5pcs/ Carton dimension 52cmx34cmx31cm / Gross weight 15kg 10pcs/ Carton dimension 60cmx51cmx36cm / Gross weight 30kg

The data above is only for reference and any change of them will not be informed in advance. For more detailed technical inquiries, please feel free to call the Technical Department of our company.