


QH-D5004AH

1080N AHD DVR


QIHAN
Creation for Intelligent Life



Feature

- 4CH 1080N AHD DVR, 4/1 Audio in/out, HDMI/VGA/BNC Video Out, 1 SATA Port, DC12V

Dimensions



Unit: mm

Technical Specifications

Model NO.	QH-D5004AH
OPERATION SYSTEM	LINUX
VIDEO/AUDIO	
VIDEO SYSTEM	NTSC/PAL Switch Selectable
VIDEO INPUT	BNC*4, 1.0Vp-p, 75ohm
CVBS OUTPUT	1 CVBS Output
HDMI OUTPUT	1 HDMI Output
VGA OUTPUT	1 VGA Output
AUDIO INPUT / OUTPUT	4CH, RCA / 1CH, RCA
TALK BACK	YES
CONTROL	
MOUSE	2*USB2.0
IR CONTROLLER	YES
STORAGE	
BUILD IN INTERFACE	SATA *1(1*HDD 4TB)
DISPLAY	
DIVISION	1, 4
ZOOM	Preview&Playback Zoom Support
RECORDING	
COMPRESSION	H.264(High profile)
RECORDING MODE	Manual/Schedule/Motion Detection/Sensor (Optional)
ENCODING ABILITY	4*1080N@25fps
DECODING ABILITY	1*1080N@25fps
RESOLUTION	Analog : 4*1080N Hybird : 2*1080N (Analog) +2*1080P(Network)
QUALITY	Worst, Worse, Bad, Normal, Better, Best
PLAYBACK	
SYNC PLAYBACK	1
SPEED	Normal, FF(1X, 2X, 4X, 8X), Slow (1/2X, 1/4X, 1/8X)
SEARCH METHOD	Time, Event, Channels and Calendar
COMMUNICATION	
REMOTE ACCESS	IE (10.0 and below), ISS (Windows XP/Win7/Win8/Win10), ISS Mobile2 (IOS, Android)
REMOTE OPERATION	Remote View, Remote Playback, Remote Setup
NETWORK SERVICE	TCP/IP, PPPOE, DDNS, FTP, NTP UPNP
MOBILE DEVICE	iPone, iPad, Android
WAN RJ45	10/100Mbit/s
3G EXTERNAL MODULE	Yes, with USB 2.0 Port
WIFI EXTERNAL MODULE	Yes, with USB 2.0 Port, 100Meters
GUI INTERFACE	Supported GUI 16 Bit True Color
PTZ PROTOCOL	PELCO-D, PELCO-P, etc 17 kinds of protocol
BACKUP	
EXTERNAL	2*USB2.0
NETWORK	YES
FILE FORMAT	AVI
GENERAL	
RS-485	1
UNIT DIMENSION(mm)	260(L) x 44(H) x 221(W)
OPERATION TEMPERATURE	10°~ 40°
WORKING HUMIDITY	10% ~ 90%
POWER CONSUMPTION	DC 12V,2A, <6W (Exclude HDD)