

IR Dome Camera

Features

- Sony Super HAD CCD Sensor
- Built-in Vari-Focal DC Drive Lens
- Day & Night (IR-Cut filter Removable, ICR)
- 3-Axis Mechanism for free lens rotation
- Built-in 24 pieces IR-LED
- Effective range up to 20M







RYK-2Sxx



RYK-2Hxx



RYK-2Kxx



Option :



RYK-8719-3
L Type Bracket

Model No.	RYK-2S49LVR3	RYK-2S85LVR3	RYK-2S49XLVR3	RYK-2S85XLVR3
	RYK-2H49LVR3/1	RYK-2H85LVR3/1	RYK-2H49XLVR3/1	RYK-2H85XLVR3/1
	RYK-2K49LVR3/1	RYK-2K85LVR3/1	RYK-2K49XLVR3/1	RYK-2K85XLVR3/1
Image Device	1/3" Color Sony Super HAD	1/3" Color Sony Super HAD (Hi-Res.)	1/3" Color Sony EX-View HAD	1/3" Color Sony EX-View HAD (Hi-Res.)
Picture Elements	NTSC:510x492, PAL:500x582	NTSC:768x494, PAL:752x582	NTSC:510x492, PAL:500x582	NTSC:768x494, PAL:752x582
Resolution	380 TVL	470 TVL	380 TVL	470 TVL
Min. Illumination	0.2 Lux / F2.0 (Day), 0 Lux (IR On)	0.3 Lux / F2.0 (Day), 0 Lux (IR On)	0.05 Lux / F2.0 (Day), 0 Lux (IR On)	0.15 Lux / F2.0 (Day), 0 Lux (IR On)
S/N Ratio	More than 48dB			
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/110,000			
Flickless Mode	On/Off (NTSC:1/100, PAL:1/120)			
Gamma	0.45			
Iris Control	DC Drive			
Lens Furnished	Vari-Focal 3.7~12mm (ICR) / F1.6~3.0, Wide:71.6°x55.8°, Tele:23.8°x17.9° (HxV)			
White Balance	Auto			
Gain Control	High / Low			
Back Light Comp.	On / Off			
Sync. System	Internal			
Video Output	1 Vp-p / 75 Ohms			
Infrared Luminary	24 pieces IR-LED			
Wavelength	850 nm			
Illumination Distance	20 M			
Power Supply	DC12V±10%			
Power Consumption	IR On: 425mA max. IR Off: 117mA max.	IR On: 400mA max. IR Off: 200mA max.	IR On: 425mA max. IR Off: 117mA max.	IR On: 400mA max. IR Off: 200mA max.
Operating Temp.	-10°C ~ 50°C			