

DynaHawk™ W3 Series

Full HD Multiple Streams Light Dome IP Camera




The IP Camera features decent low light performance, various video resolution combinations, multiple video compression formats, etc. It supports true day / night and 3DNR function, which display clear images in low light conditions. Moreover, the proprietary SPQ (Smart Picture Quality) function allows delivering quality images especially under intensive motion and low light conditions. With the built-in IR LED module, the IP Camera makes visibility in nearly total darkness.

With H.264 High / Main / Baseline profile and MJPEG video compression formats support, it is beneficial for optimization of bandwidth and network resources. Video quad-stream support allows various surveillance applications and facilitates working with other back-end devices.

■ Key Features

- Progressive Scan CMOS Sensor
- Quad Streams Compression- H.264 Baseline / Main / High Profile + MJPEG
- Multi-language Support
- Tampering Alarm
- Remote Zoom & Focus (Motorized Lens)*
- Wide Dynamic Range
- Motion Detection
- Privacy Masks
- Smart Picture Quality / 3D Noise Reduction
- Vertical View Mode (Image rotation by 90 degrees)
- Smart IR Mode
- Network Failure Detection
- Day/Night (ICR)
- IR LED Module (working distance up to 25 m)*
- microSD Support
- BNC analog output
- ONVIF Support



DynaHawk™ W3 Series - Light Dome IP Camera

Camera		W2V1-3	W2S1-3
Image Sensor		1/2.7" Progressive CMOS	1/2.8" Sony Progressive CMOS
Effective Pixels		1920(H) x 1080(V)	
Minimum Illumination		Motorized & Vari-focal: 0.2 lux (Color)/ 0.02 lux (B/W) 3x AF: 0.2 lux (Color)/ 0.02 lux (B/W)	Motorized & Vari-focal: 0.2 lux (Color)/ 0.02 lux (B/W) 3x AF: 0.2 lux (Color)/ 0.02 lux (B/W)
Shutter Speed		1 ~ 1/10000 sec.	
Lens		Vari-focal / Motorized / Auto Focus	
Focal Length		Motorized & Vari-focal : 3 - 10.5 mm 3x AF: 3 - 9mm	
F Number		Motorized & Vari-focal: F1.4 3x AF: F1.2	
FOV		Motorized & Vari-focal: 103° (Wide) ; 34.35 (Tele) 3x AF: 108° (Wide); 41° (Tele)	Motorized & Vari-focal: 90° (Wide) ; TBD (Tele) 3x AF: 96.12° (Wide); 32.04° (Tele)
Operation		English / French / German / Italian / Japanese / Korean / Portuguese / Russian / Simplified Chinese / Spanish / Traditional Chinese	
Image Setting	IRIS Control*	3x: P-IRIS & DC-IRIS Motorized & Vari-focal: DC-IRIS	
	Backlight Compensation	On / Off	
	White Balance	Manual / AWB / ATW / One Push	
	3D Noise Reduction	On / Off	
	Wide Dynamic Range	On / Off	
	Privacy Mask	On / Off	
	Brightness	Manual	
	Exposure	Auto / Manual	
	Sharpness	Manual	
	Contrast	Manual	
	Saturation	Manual	
	Hue	Manual	
	Digital Zoom	Support	
	Motion Detection	On / Off / By Schedule	
	Privacy Mask Type	Color	
	ICR	Auto / On / Off / Smart	
	ICR+IR LED*	Auto / LED On / LED Off / Smart IR / Light Sensor	
Audio	Tampering Alarm	On / Off / By Schedule	
	Two-way Audio	Line in / Line Out	
	Compression	G.711/G.726	
Network		RJ-45, 10/100 Mbps Ethernet	
Video Compression		H.264 (MPEG-4 Part 10/AVC) / MJPEG	
Video Streaming		Dual Streams - H.264 + MJPEG / H.264 + H.264 Quad Streams - H.264*3 + MJPEG / H.264*4	
Video Resolution		H.264- Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF MJPEG- Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF	
Frame Rate		Single stream - 1080p (30/25 fps) Dual Streams - 1080p (30 / 25 fps) + D1 (30 / 25 fps)	
Protocol		ARP, IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF	
Security		HTTPS / IP Filter / IEEE 802.1X	
Alarm	Input	1 Set 5V 10kΩ pull up	
	Output	1 Set Photo Relay Output 300V DC/AC	
Event Notification		HTTP / FTP / SMTP	
Micro SD		microSDHC 32GB support	
Supported Web Browser		Internet Explorer (6.0+) / Chrome / Firefox / Safari	
User Account		20	
Password Levels		User and Administrator	
Mechanical		Working Distance up to 25 m	
Built-in IR Illuminator*	Wavelength	850 nm	
	Number of LEDs	24	
LED Indicator		Power / Link / ACT	
Connectors	Alarm	4 Pin Terminal Block	
	Power	3 Pin Terminal Block	
	Ethernet	RJ-45	
	Analog Video	1.0 Vp-p / 75 Ω, BNC	
	Audio*	Line in / Line Out	
General		Operating Temperature -10°C ~ 50°C (14° ~ 122° F)	
Humidity		10% ~ 90%, No Condensation	
Dimension		Ø 149 x 131 mm (Ø 5.9 x 5.2 in.)	
Weight		700 g (1.5 lb)	
Power Source		DC 12V / AC 24V / PoE	
Power Consumption		System: 5 W (Built-in IR Illuminator: +3 W, Motorized Lens: +3.6 W, 3x lens: +3W)	
Regulatory		CE / FCC	

* mark for optional items

Product specification and availability are subject to change without notice.



DYNACOLOR, INC.

No. 116, Jou Tz Street, Neihu, Taipei 114, Taiwan

TEL: (886)2-2659-8898

FAX: (886)2-2659-8868

http://www.dynacolor.com.tw

info@dynacolor.com.tw