

DynaHawk™ W5 Series


Full HD Multiple Streams Bullet IP Camera



Network DynaHawk W5 series Full HD Multiple Streams Bullet IP Cameras support both H.264 and MJPEG compression. In addition to the superior Full HD image quality, the built-in IR LEDs ensure the night vision even when it is under zero lux. The cable management bracket not only saves the time on installation but also keeps the cables from sabotage. With the international IP66 rating and weather-proof design, the Bullet IP camera can perform stably in harsh environments.

Key Features

- Progressive Scan CMOS Sensor
- Quad Streams Support
- Dual Streams, Full HD 1080P Real-time + D1 Real-time
- Quad Streams Compression: H.264 Baseline / Main / High Profile + MJPEG
- Multi-language Support
- Tampering Alarm
- Wide Dynamic Range
- Remote Zoom & Focus (Motorized Lens)*
- Motion Detection
- Privacy Masks
- Color NR / 2DNR / 3DNR
- Vertical View Mode (Image rotation by 90 degrees)
- Smart IR Mode
- Network Failure Detection
- Day/Night (ICR)
- IR LED Module (working distance up to 25 m)
- micro SD Support
- Weatherproof (IP66 International)
- Sunshield
- Integrated Mounting Bracket with Cable Management
- ONVIF Support



DynaHawk™ W5 Series - Bullet IP Camera

Camera		W1S1-5		W1V1-5	
Image Sensor	1/2.8" Progressive CMOS		1/2.7" Progressive CMOS		
Effective Pixels			1920(H) x 1080(V)		
Shutter Speed			1 - 1/10000 sec.		
Lens					
Lens type	Motorized vari-focal	Auto focus	Motorized vari-focal	Auto Focus	
Focal Length	3 - 10.5 mm	3 - 9 mm	3 - 10.5 mm	3 - 9 mm	
F Number	F 1.4	F1.2 (Wide); F2.1 (Tele)	F 1.4	F1.2 (Wide); F2.1 (Tele)	
FOV	90° (Wide); TBD° (Tele)	96° (Wide); 32° (Tele)	93.9° (Wide); TBD° (Tele)	108° (Wide); 41° (Tele)	
Minimum Illumination	0.2 lux (Color); 0.02 lux (B/W)	0.2 lux (Color); 0.02 lux (B/W)	0.2 lux (Color); 0.02 lux (B/W)	0.2 lux (Color); 0.02 lux (B/W)	
Operation					
Multiple Languages	English / French / German / Italian / Japanese / Korean / Portuguese / Russian / Simplified Chinese / Spanish / Traditional Chinese				
Image Setting	Iris control*	DC Iris / P Iris			
	Backlight Compensation	On / Off			
	White Balance	Manual / AWB / ATW / One Push			
	Noise Reduction	3D	On / Off		
	Wide Dynamic Range	On / Off			
	Privacy Mask	On / Off			
	Brightness	Manual			
	Exposure	Auto / Manual			
	Sharpness	Manual			
	Contrast	Manual			
	Saturation	Manual			
	Hue	Manual			
	Digital Zoom	Support			
	Motion Detection	On / Off			
	Privacy Mask Type	Color			
ICR + IR LED	Auto / LED On / LED Off / Smart IR / Light Sensor				
Tampering Alarm	On / Off				
Audio	Two-way Audio	Line in / Line Out			
	Compression	G.711 / G.726			
Network					
Interface	RJ-45, 10/100 Mbps Ethernet				
Video Compression	H.264 (MPEG-4 Part 10/AVC) / MJPEG				
Video Streaming	Dual Streams H.264 + MJPEG / H.264 + H.264 Quad Streams H.264 * 3 + MJPEG / H.264 * 3 + H.264				
Video Resolution	H.264- Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF MJPEG- Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF				
Frame Rate	Single Stream - 1080p (13/15fps) Dual Streams - 1080p (13/15 fps) + 720p (25/30 fps)				
Protocol	ARP, IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF				
Security	HTTPS / IP Filter / IEEE 802.1x				
Alarm	Input	1 Set 5V 10kΩ pull up			
	Output	1 Set Photo Relay Output 300V DC/AC			
Event Notification	HTTP / FTP / SMTP				
Micro SD	microSDHC 32GB support				
Supported Web Browser	Internet Explorer (6.0+) / Chrome / Firefox / Safari				
User Account	20				
Password Levels	User and Administrator				
Mechanical					
Built-in IR Illuminator	Working Distance	up to 25 m			
	Wavelength	850 nm			
	Number of LEDs	24			
LED Indicator	Power / Link / ACT				
Connectors	Alarm	4 Pin Terminal Block			
	Power	3 Pin Terminal Block			
	Ethernet	RJ-45			
	Analog Video	1.0 Vp-p / 75 Ω, BNC			
	Audio	Line in / Line Out			
General					
Operating Temperature	w/o Heater: -10° C - 50° C (14° - 122° F) w/Heater: powered by DC12V: -30° C - 50° C (-22° - 122° F) w/Heater: powered by AC24V/PoE+: -40° C - 50° C (-40° - 122° F)				
	Humidity: 10% to 90%, no condensation				
Humidity	10% - 90%, No Condensation				
Weatherproof Standard	IP66				
Dimension	ø 84 x 260 mm (ø 3.3 x 7.1 in.)				
	ø 90 x 270 mm (ø 3.3 x 7.6 in.) w/ Sunshield				
Weight	940 g (2.07 lb)				
Power Source	DC 12V / AC 24V / PoE or AC 24V / PoE+				
Power Consumption	System: 5 W				
	(Built-in IR Illuminator: +3 W, Motorized Lens/Auto focus lens: +3.6 W, Heater: +12 W)				
Regulatory	CE / FCC / RoHS				

* mark for optional items
Product specification and availability are subject to change without notice.



DYNACOLOR, INC.
No. 116, Jou Tz Street, Neihu, Taipei 114, Taiwan
TEL: (886)2-2659-8898 FAX: (886)2-2659-8868
<http://www.dynacolor.com.tw> info@dynacolor.com.tw