

# DynaHawk™ WH Series


Full HD Multiple Streams Micro Box IP Camera (WiFi / PoE)



The Full HD Multiple Streams Micro Box IP Camera is not only an easy setup camera, but a versatile solution for homes and small offices. For WiFi model, users can install the wireless IP camera in any place with Wi-Fi access. In addition, the both type of micro box camera has built-in microphone and speaker which allows two-way audio communication. For low light environments, the IP camera has incorporated Day/Night ICR technologies to capture clear images. 2 and 3 Megapixel resolution is supported for providing high definition images. Quad Streams Compression (H.264 Baseline / Main / High Profile + MJPEG) are available for efficient bandwidth and storage management. Users now can remotely and clearly watch over their families and homes via mobile devices while they are at work or even traveling.

## Key Features

- Progressive Scan Sony CMOS Sensor
- 2M/3M Resolution
- Quad Streams Support
- Dual streams- Full HD 1080P Real-time + D1 Real-time
- Quad Streams Compression- H.264 Baseline / Main / High Profile + MJPEG
- Multi-language Support
- Wireless Network Support (WiFi model only)
- Wide Dynamic Range
- Built-In Microphone and Speaker\*
- Motion Detection
- Privacy Masks
- Smart Picture Quality / 3D Noise Reduction
- Smart IR Mode
- Day/Night (ICR)
- IR LED Module (working distance up to 5 m)\*
- microSD Support
- ONVIF Support



# DynaHawk™ WH Series - Micro Box IP Camera

Camera		W3S1-H
Image Sensor		1/2.8" Progressive CMOS
Effective Pixels		2048(H) x 1536(V)
Minimum Illumination		TBD
Shutter Speed		1 ~ 1/10000 sec.
Lens		
Lens		Board lens
Focal Length		2.8 mm / 3.6 mm
F Number		F 2.0 / F 1.8
FOV		94.36° / 75.3°
Operation		
Multiple Languages	English / French / German / Italian / Japanese / Korean / Portuguese / Russian / Simplified Chinese / Spanish / Traditional Chinese	
Backlight Compensation		On / Off
White Balance		Manual / AWB / ATW / One Push
3D Noise Reduction		On / Off
Wide Dynamic Range		On / Off
Privacy Mask		On / Off
Brightness		Manual
Exposure		Auto / Manual
Sharpness		Manual
Contrast		Manual
Saturation		Manual
Hue		Manual
Digital Zoom		Support
Motion Detection		On / Off / By Schedule
Privacy Mask Type		Color
ICR		Auto / On / Off / Smart
ICR+IR LED*		Auto / LED On / LED Off / Smart IR / Light Sensor
Tampering Alarm		On / Off / By Schedule
Two-way Audio		Embedded Mic in / Embedded Speaker Out*
Audio		Compression G.711/G.726
Network		
Interface		RJ-45, 10/100 Mbps Ethernet
Video Compression		H.264 (MPEG-4 Part 10/AVC) / MJPEG
Video Streaming		Dual Streams H.264 + MJPEG / H.264 + H.264 Quad Streams H.264*3 + MJPEG / H.264*4
Video Resolution		H.264- 3M / Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF MJPEG- Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF
Frame Rate		Dual Streams : 2048 x 1536 (15 fps) + 720p (15 fps) 1080p (25 / 30 fps) + D1 (25 / 30 fps)
Protocol		ARP, IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF
Security		PoE: HTTPS / IP Filter / IEEE 802.1X WiFi: HTTPS / IP Filter / IEEE 802.1X (WPA, WPA2)/Shared Key/Pair-wise Key
Alarm	Input	1 Set 5V 10kΩ pull up
	Output	1 Set Photo Relay Output 300V DC/AC
Event Notification		HTTP / FTP / SMTP
Micro SD		microSDHC 32GB support
Supported Web Browser		Internet Explorer (6.0+ ) / Chrome / Firefox / Safari
User Account		20
Password Levels		User and Administrator
Mechanical		
Built-in IR Illuminator*	Working Distance	up to 5 m
	Wavelength	850 nm
	Number of LEDs	2
LED Indicator		PoE: Power / Link / ACT ; WiFi: Power (Green) / WiFi (Orange)
Connectors	Alarm	4 Pin Terminal Block
	Power	PoE: DC Jack / WiFi: Micro USB ( with 1A USB charger )
	Ethernet	PoE: RJ-45 ; WiFi: N/A
General		
Operating Temperature		-10°C ~ 50°C (14° ~ 122° F)
Humidity		10% ~ 90%, No Condensation
Weatherproof Standard*		IP66
Dimension		96.51 x 56 x 61.4 mm (3.78 x 2.2 x 2.42 in.)
Weight		120g
Power Source		PoE: DC 12V / PoE ; WiFi: 1A USB charger
Power Consumption		WiFi: System 3.2 W (Built-in IR Illuminator: +0.8W) PoE: System 3.4 W (Built-in IR Illuminator: +1W)
Regulatory		CE / FCC

\* mark for optional items

Product specification and availability are subject to change without notice.



DYNACOLOR, INC.

No. 116, Jou Tz Street, Neihu, Taipei 114, Taiwan

TEL: (886)2-2659-8898

FAX: (886)2-2659-8868

http://www.dynacolor.com.tw

info@dynacolor.com.tw