


















Main Features

- H.264 video compression
- 120 CIF fps recording frame rate
- Video files sent along with email alert and notification by MSN
- SATA II compatible HDD & E-SATA for external HDD
- Intelligent 3G/GPRS mobile surveillance
- Support smart search function for faster and easier playback retrieval
- Picture-in-picture display & channel screen popup on motion/sensor
- Optional 1-to-8 remote controller for access up to 8 DVRs with one single remote controller
- Role-based multiple network users access to exclusive channel view & operation
- Provide optional touch screen display integrated with LCD
- Provide disk array option with mirror functionality to provide additional storage archival without missing any display images
- Provide Graphical User Interface (GUI) and mouse access for easier and user friendly configuration and operation
- Remote independent operation


Interface

Front Panel Layout



1-9 Function Keys	on Keys 10-13 Direction Keys		15 IR Sensor
16 USB 2.0 Port	17 CD/DVD-RW		

Back Panel Layout



1 MAIN Monitor	2 SPOT Monitor	3 VIDEO IN	4 AUDIO IN
5 AUDIO OUT	6 VGA	7 E-SATA	8 Fan
9 EXTERNAL I/O	10 LAN	11 NTSC / PAL Switch	12 DC 12V

Specifications

Model No.		SDVR-410			
			Video		
Mode		Pentaplex (Live, Record, Playback, Backup, and Network)			
Video Input			BNCx4 1.0 Vp-p±10% Composite, 75 Balanced		
Video Loop Out		N/A			
Video Output	Main Monitor		BNCx1 2Vp-p Composite, 75 Balanced		
	Spot Monitor		BNCx1		
	S-Video		N/A		
	VGA (Optional)		VGAx1, 1024x768 pixels		
			Audio		
Audio Input			RCAx4		
Audio Output			RCAx1		
Audio Backup		YES			
Audio Compression		G.711			
			Display		
Image System			NTSC	PAL	
Display Resolution Rate	n &	D1	120fps (720x480)	100fps (720x576)	
Split Screen		1/4/SEQ			
Mode		Digital Zoomx2, PIP, Auto SEQ			
			Recording		
Compression Type			H.264 (Internet Transmission: H.264)		
- · · · · · ·	0	D1	up to 30fps (720x480)	up to 25fps (720x576)	
Recording Resolu	ution &	Half D1	up to 60fps (720x240)	up to 50fps (720x288)	
Rate		CIF	up to 120fps (352x240)	up to 100fps (352x288)	
Image Quality			5 Levels (Highest, High, Normal, Low, Lowest)		
Recording Mode			Normal, Event (Motion, Alarm), Schedule, Holiday		
			Playback		
Screen Display			1, 4		
		D1	up to 30fps (720x480)	up to 25fps (720x576)	
Playback Resolut Rate	tion &	Half D1	up to 60fps (720x240)	up to 50fps (720x288)	
		CIF	up to 120fps (352x240)	up to 100fps (352x288)	
Playback Speed		Normal, REW, FF (2, 4, 8, 16, 32, 64), Pause			
Search Method		Time, Event			
		Stora	ge & Backup Device		
Internal HDD Support (SATA/SATA II)		Support up to 2 HDDs or 1 HDD & 1 internal DVD-write			
External SATA		YES for RAID			
Network		Remote Backup			
USB Backup		1 at Front Panel			

OSD & DVR Control				
GUI	YES			
Multi Language	12 (English, French, German, Greek, Japanese, Italian, Polish, Portuguese, Russian, Spanish, Simplified Chinese, Traditional Chinese)			
USB Mouse	YES			
IR Remote Control	YES & 1-to-8 Remote Control (Optional)			
DVR Control Panel	YES			
Remote Software	Licensed Software Application, IE Browser & CMS			
Touch Panel	Supports USB Touch Panel (Specified LCD Models)			
	Communication			
Ethernet	1 RJ45, 10/100 Mbps			
Network Service	TCP/IP, SMTP, HTTP, DHCP, ADSL, LAN, DDNS			
Multi-Remote Client	YES (5 Clients Accessible)			
3G/GPRS	Supports Windows Mobile 5.0/6.0, Symbian & iPhone			
	Alarm			
Sensor Input	4 In (NO/NC)			
Alarm Output	1 Relay Out (NO/NC)			
Motion Detection	YES (16x12 Grids per Camera for All Channels)			
Motion Detection Sensitivity	1~15			
Video Loss Detection	YES			
Pre-alarm Recording	16MB (10 sec)			
Post-alarm Recording	1-999 sec			
Buzzer	YES			
Remote Alarm Notification	J-PEG File sent by e-mail; Message Notified by MSN & 3G Mobile Phone			
Sett	up & Other Functions			
PTZ Control	Supports PELCO-D, PELCO-P, KND, Li-Lin, LG, Samsung, AV Tech			
RS-485	YES			
Password Control	YES			
Key-lock	YES			
Firmware Upgrade	via USB			
os	Others			
	Embedded Linux			
Power Input	External Adaptor, AC100-240V/in, DC 12V(5A/60W)			
Dimension				
Weight	3kg (Including 1 HDD or CD/DVD-RW)			
Operation Temperature	5°C~ + 40°C			
Humidity	Less than 90%			
Watermark	N/A			
Recovery	Watchdog			
Certificates	CE, FCC, RoHS			
SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE				

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE



CD/DVD-RW Backup